



18

EN 12566-1

DECLARATION OF PERFORMANCE

N°RIF_EPURBLOC®_115_00

- 1- Unique identification code of the product-type:**
Small wastewater treatment systems up to 50 PT: prefabricated septic tanks
- 2- Intended uses(s):**
Treatment of domestic wastewater for a population up to 50 PTE
- 3- Manufacturer:**
RIKUTEC France, 2A rue de Sarreguemines, F – 67320 DRULINGEN
- 4- Authorised representative:**
Not applicable
- 5- System(s) of Assessment and verification of constancy of performance (AVCP):**
3
- 6- Harmonized standard:**
EN 12566-1+A1
Notified body:
CERIB n°1164
- 7- Declared performances:**
See annex
- 8- Appropriate technical documentation and/or specific technical documentation.**
User's guide A23

The performance of the product identified above is in conformity with the set of declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Marc SENGELIN
R&D, Standardization and Agreement Manager.

Drulingen, 3rd January 2020

ANNEX

ESSENTIAL CHARACTERISTICS	PERFORMANCES			HARMONISED TECHNICAL SPECIFICATION
Treatment efficiency (hydraulic efficiency)	<i>Model of the range</i>	<i>Hydraulic efficiency</i>		EN 12566-1+A1:2004
	AT 115 2000 L	≤ 13,00 g of beads		
	AT 115 3000 L			
Nominal capacity (treatment capacity)	<i>Model of the range</i>	<i>Nominal capacity</i>		
	AT 115 2000 L	2 m ³		
	AT 115 3000 L	3 m ³		
Watertightness	Conform			
Durability	Conform			
Structural behaviour (Crushing resistance and maximum load deformation)	<i>Model of the range</i>	<i>Maximum permissible backfill height above the tank</i>	<i>Soil conditions with the maximum height of the water table from the base of the tank.</i>	
	AT 115 2000 L	0,80 m	DRY	
	AT 115 3000 L			